

STANDARD ITS-90 THERMOCOUPLE TABLES

The Instrument Society of America (ISA) has assigned standard letter designations to a number of thermocouple types having specified emf-temperature relations. These designations and the approximate metal compositions which meet the required relations, as well as the useful temperature ranges, are given below:

Type B	(Pt + 30% Rh) vs. (Pt + 6% Rh)	0 to 1820°C
Type E	(Ni + 10% Cr) vs. (Cu + 43% Ni)	-270 to 1000°C
Type J	Fe vs. (Cu + 43% Ni)	-210 to 1200°C
Type K	(Ni + 10% Cr) vs. (Ni + 2% Al + 2% Mn + 1% Si)	-270 to 1372°C
Type N	(Ni + 14% Cr + 1.5% Si) vs. (Ni + 4.5% Si + 0.1% Mg)	-270 to 1300°C
Type R	(Pt + 13% Rh) vs. Pt	-50 to 1768°C
Type S	(Pt + 10% Rh) vs. Pt	-50 to 1768°C
Type T	Cu vs. (Cu + 43% Ni)	-270 to 400°C

The compositions are given in weight percent, and the positive leg is listed first. It should be emphasized that the standard letter

designations do not imply a precise composition but rather that the specified emf-temperature relation is satisfied.

The first set of tables below lists, for each thermocouple type, the emf as a function of temperature on the International Temperature Scale of 1990 (ITS-90). The coefficients in the equation used to generate the table are also given. The second set of tables gives the inverse relationships, i.e., the coefficients in the polynomial equation which expresses the temperature as a function of thermocouple emf. The accuracy of these equations is also stated.

Further details and tables at closer intervals may be found in Reference 1.

References

1. Burns, G. W., Seroger, M. G., Strouse, G. F., Croarkin, M. C., and Guthrie, W. F., *Temperature-Electromotive Force Reference Functions and Tables for the Letter-Designated Thermocouple Types Based on the ITS-90*, Natl. Inst. Stand. Tech. (U.S.) Monogr. 175, 1993.
2. Schooley, J. F., *Thermometry*, CRC Press, Boca Raton, FL, 1986.

Type B Thermocouples: emf-Temperature (°C) Reference Table and Equations

Thermocouple emf as a Function of Temperature in Degrees Celsius (ITS-90)

°C	emf in Millivolts										Reference junctions at 0 °C				
	0	10	20	30	40	50	60	70	80	90	110	120	130	140	150
0	0.000	-0.002	-0.003	-0.002	-0.000	0.002	0.006	0.011	0.017	0.025	0.033	0.041	0.049	0.057	0.065
100	0.033	0.043	0.053	0.065	0.078	0.092	0.107	0.123	0.141	0.159	0.178	0.196	0.214	0.232	0.251
200	0.178	0.199	0.220	0.243	0.267	0.291	0.317	0.344	0.372	0.401	0.431	0.460	0.489	0.518	0.547
300	0.431	0.462	0.494	0.527	0.561	0.596	0.632	0.669	0.707	0.746	0.787	0.826	0.865	0.904	0.943
400	0.787	0.828	0.870	0.913	0.957	1.002	1.048	1.095	1.143	1.192	1.242	1.281	1.320	1.359	1.400
500	1.242	1.293	1.344	1.397	1.451	1.505	1.561	1.617	1.675	1.733	1.792	1.850	1.908	1.966	2.024
600	1.792	1.852	1.913	1.975	2.037	2.101	2.165	2.230	2.296	2.363	2.431	2.499	2.566	2.633	2.700
700	2.431	2.499	2.569	2.639	2.710	2.782	2.854	2.928	3.002	3.078	3.154	3.230	3.306	3.383	3.460
800	3.154	3.230	3.308	3.386	3.466	3.546	3.626	3.708	3.790	3.873	3.957	4.040	4.123	4.206	4.289
900	3.957	4.041	4.127	4.213	4.299	4.387	4.475	4.564	4.653	4.743	4.834	4.923	5.012	5.101	5.190
1000	4.834	4.926	5.018	5.111	5.205	5.299	5.394	5.489	5.585	5.682	5.780	5.878	5.975	6.072	6.169
1100	5.780	5.878	5.976	6.075	6.175	6.276	6.377	6.478	6.580	6.683	6.786	6.885	6.983	7.081	7.179
1200	6.786	6.890	6.995	7.100	7.205	7.311	7.417	7.524	7.632	7.740	7.848	7.956	8.064	8.172	8.280
1300	7.848	7.957	8.066	8.176	8.286	8.397	8.508	8.620	8.731	8.844	8.956	9.068	9.180	9.292	9.404
1400	8.956	9.069	9.182	9.296	9.410	9.524	9.639	9.753	9.868	9.984	10.099	10.215	10.327	10.439	10.551
1500	10.099	10.215	10.331	10.447	10.563	10.679	10.796	10.913	11.029	11.146	11.263	11.378	11.494	11.610	11.726
1600	11.263	11.380	11.497	11.614	11.731	11.848	11.965	12.082	12.199	12.316	12.433	12.549	12.666	12.782	12.898
1700	12.433	12.549	12.666	12.782	12.898	13.014	13.130	13.246	13.361	13.476	13.591	13.606	13.722	13.838	13.954
1800	13.591	13.706	13.820												

Temperature ranges and coefficients of equations used to compute the above table: The equations are of the form: $E = c_0 + c_1 t + c_2 t^2 + c_3 t^3 + \dots + c_n t^n$, where E is the emf in millivolts, t is the tem-

perature in degrees Celsius (ITS- 90), and $c_0, c_1, c_2, c_3, \dots$ etc. are the coefficients. These coefficients are extracted from Reference 1.

0 °C to 630.615 °C		630.615 °C to 1820 °C	
c_0	= 0.000 000 000 0	-3.893 816 862 1 ...	
c_1	= -2.465 081 834 6 $\times 10^{-4}$	2.857 174 747 0 $\times 10^{-2}$	
c_2	= 5.904 042 117 1 $\times 10^{-6}$	-8.488 510 478 5 $\times 10^{-5}$	
c_3	= -1.325 793 163 6 $\times 10^{-9}$	1.578 528 016 4 $\times 10^{-7}$	
c_4	= 1.566 829 190 1 $\times 10^{-12}$	-1.683 534 486 4 $\times 10^{-10}$	
c_5	= -1.694 452 924 0 $\times 10^{-15}$	1.110 979 401 3 $\times 10^{-13}$	
c_6	= 6.299 034 709 4 $\times 10^{-19}$	-4.451 543 103 3 $\times 10^{-17}$	
c_7	=	9.897 564 082 1 $\times 10^{-21}$	
c_8	=	-9.379 133 028 9 $\times 10^{-25}$	

Type E Thermocouples: emf-Temperature (°C) Reference Table and Equations

Thermocouple emf as a Function of Temperature in Degrees Celsius (ITS-90)

emf in Millivolts											Reference junctions at 0 °C			
°C	0	-10	-20	-30	-40	-50	-60	-70	-80	-90	-100			
-200	-8.825	-9.063	-9.274	-9.455	-9.604	-9.718	-9.797	-9.835						
-100	-5.237	-5.681	-6.107	-6.516	-6.907	-7.279	-7.632	-7.963	-8.273	-8.561	-8.825			
0	0.000	-0.582	-1.152	-1.709	-2.255	-2.787	-3.306	-3.811	-4.302	-4.777	-5.237			
°C	0	10	20	30	40	50	60	70	80	90	100			
0	0.000	0.591	1.192	1.801	2.420	3.048	3.685	4.330	4.985	5.648	6.319			
100	6.319	6.998	7.685	8.379	9.081	9.789	10.503	11.224	11.951	12.684	13.421			
200	13.421	14.164	14.912	15.664	16.420	17.181	17.945	18.713	19.484	20.259	21.036			
300	21.036	21.817	22.600	23.386	24.174	24.964	25.757	26.552	27.348	28.146	28.946			
400	28.946	29.747	30.550	31.354	32.159	32.965	33.772	34.579	35.387	36.196	37.005			
500	37.005	37.815	38.624	39.434	40.243	41.053	41.862	42.671	43.479	44.286	45.093			
600	45.093	45.900	46.705	47.509	48.313	49.116	49.917	50.718	51.517	52.315	53.112			
700	53.112	53.908	54.703	55.497	56.289	57.080	57.870	58.659	59.446	60.232	61.017			
800	61.017	61.801	62.583	63.364	64.144	64.922	65.698	66.473	67.246	68.017	68.787			
900	68.787	69.554	70.319	71.082	71.844	72.603	73.360	74.115	74.869	75.621	76.373			
1000	76.373													

Temperature ranges and coefficients of equations used to compute the above table: The equations are of the form: $E = c_0 + c_1 t + c_2 t^2 + c_3 t^3 + \dots + c_n t^n$, where E is the emf in millivolts, t is the tem-

perature in degrees Celsius (ITS- 90), and c_0, c_1, c_2, c_3 , etc. are the coefficients. These coefficients are extracted from Reference 1.

-270 to 0°C		0°C to 1000°C	
c_0	= 0.000 000 000 0 ...	0.000 000 000 0 ...	
c_1	= 5.866 550 870 8 $\times 10^{-2}$	5.866 550 871 0 $\times 10^{-2}$	
c_2	= 4.541 097 712 4 $\times 10^{-5}$	4.503 227 558 2 $\times 10^{-5}$	
c_3	= -7.799 804 868 6 $\times 10^{-7}$	2.890 840 721 2 $\times 10^{-8}$	
c_4	= -2.580 016 084 3 $\times 10^{-8}$	-3.305 689 665 2 $\times 10^{-10}$	
c_5	= -5.945 258 305 7 $\times 10^{-10}$	6.502 440 327 0 $\times 10^{-13}$	
c_6	= -9.321 405 866 7 $\times 10^{-12}$	-1.919 749 550 4 $\times 10^{-16}$	
c_7	= -1.028 760 553 4 $\times 10^{-13}$	-1.253 660 049 7 $\times 10^{-18}$	
c_8	= -8.037 012 362 1 $\times 10^{-16}$	2.148 921 756 9 $\times 10^{-21}$	
c_9	= -4.397 949 739 1 $\times 10^{-18}$	-1.438 804 178 2 $\times 10^{-24}$	
c_{10}	= -1.641 477 635 5 $\times 10^{-20}$	3.596 089 948 1 $\times 10^{-28}$	
c_{11}	= -3.967 361 951 6 $\times 10^{-23}$	
c_{12}	= -5.582 732 872 1 $\times 10^{-26}$	
c_{13}	= -3.465 784 201 3 $\times 10^{-29}$	

Type J Thermocouples: emf-Temperature (°C) Reference Table and Equations

Thermocouple emf as a Function of Temperature in Degrees Celsius (ITS-90)

emf in Millivolts											Reference junctions at 0 °C			
°C	0	-10	-20	-30	-40	-50	-60	-70	-80	-90	-100			
-200	-7.890	-8.095												
-100	-4.633	-5.037	-5.426	-5.801	-6.159	-6.500	-6.821	-7.123	-7.403	-7.659	-7.890			
0	0.000	-0.501	-0.995	-1.482	-1.961	-2.431	-2.893	-3.344	-3.786	-4.215	-4.633			

°C	emf in Millivolts										Reference junctions at 0 °C				
	0	10	20	30	40	50	60	70	80	90	100				
0	0.000	0.507	1.019	1.537	2.059	2.585	3.116	3.650	4.187	4.726	5.269				
100	5.269	5.814	6.360	6.909	7.459	8.010	8.562	9.115	9.669	10.224	10.779				
200	10.779	11.334	11.889	12.445	13.000	13.555	14.110	14.665	15.219	15.773	16.327				
300	16.327	16.881	17.434	17.986	18.538	19.090	19.642	20.194	20.745	21.297	21.848				
400	21.848	22.400	22.952	23.504	24.057	24.610	25.164	25.720	26.276	26.834	27.393				
500	27.393	27.953	28.516	29.080	29.647	30.216	30.788	31.362	31.939	32.519	33.102				
600	33.102	33.689	34.279	34.873	35.470	36.071	36.675	37.284	37.896	38.512	39.132				
700	39.132	39.755	40.382	41.012	41.645	42.281	42.919	43.559	44.203	44.848	45.494				
800	45.494	46.141	46.786	47.431	48.074	48.715	49.353	49.989	50.622	51.251	51.877				
900	51.877	52.500	53.119	53.735	54.347	54.956	55.561	56.164	56.763	57.360	57.953				
1000	57.953	58.545	59.134	59.721	60.307	60.890	61.473	62.054	62.634	63.214	63.792				
1100	63.792	64.370	64.948	65.525	66.102	66.679	67.255	67.831	68.406	68.980	69.553				
1200	69.553														

Temperature ranges and coefficients of equations used to compute the above table: The equations are of the form: $E = c_0 + c_1 t + c_2 t^2 + c_3 t^3 + \dots + c_n t^n$, where E is the emf in millivolts, t is the temperature in degrees Celsius (ITS-90), and $c_0, c_1, c_2, c_3, \dots$ etc. are the coefficients. These coefficients are extracted from Reference 1.

perature in degrees Celsius (ITS-90), and $c_0, c_1, c_2, c_3, \dots$ etc. are the coefficients. These coefficients are extracted from Reference 1.

-260°C to 760°C		760°C to 1200°C	
c_0	=	0.000 000 000 0 ...	2.964 562 568 1 $\times 10^2$
c_1	=	5.038 118 781 5 $\times 10^{-2}$	-1.497 612 778 6 ...
c_2	=	3.047 583 693 0 $\times 10^{-5}$	3.178 710 392 4 $\times 10^{-3}$
c_3	=	-8.568 106 572 0 $\times 10^{-8}$	-3.184 768 670 1 $\times 10^{-6}$
c_4	=	1.322 819 529 5 $\times 10^{-10}$	1.572 081 900 4 $\times 10^{-9}$
c_5	=	-1.705 295 833 7 $\times 10^{-13}$	-3.069 136 905 6 $\times 10^{-13}$
c_6	=	2.094 809 069 7 $\times 10^{-16}$
c_7	=	-1.253 839 533 6 $\times 10^{-19}$
c_8	=	1.563 172 569 7 $\times 10^{-23}$

Type K Thermocouples: emf-Temperature (°C) Reference Table and Equations

Thermocouple emf as a Function of Temperature in Degrees Celsius (ITS-90)

°C	emf in Millivolts										Reference junctions at 0 °C				
	0	-10	-20	-30	-40	-50	-60	-70	-80	-90	-100				
-200	-5.891	-6.035	-6.158	-6.262	-6.344	-6.404	-6.441	-6.458							
-100	-3.554	-3.852	-4.138	-4.411	-4.669	-4.913	-5.141	-5.354	-5.550	-5.730	-5.891				
0	0.000	-0.392	-0.778	-1.156	-1.527	-1.889	-2.243	-2.587	-2.920	-3.243	-3.554				
°C	0	10	20	30	40	50	60	70	80	90	100				
0	0.000	0.397	0.798	1.203	1.612	2.023	2.436	2.851	3.267	3.682	4.096				
100	4.096	4.509	4.920	5.328	5.735	6.138	6.540	6.941	7.340	7.739	8.138				
200	8.138	8.539	8.940	9.343	9.747	10.153	10.561	10.971	11.382	11.795	12.209				
300	12.209	12.624	13.040	13.457	13.874	14.293	14.713	15.133	15.554	15.975	16.397				
400	16.397	16.820	17.243	17.667	18.091	18.516	18.941	19.366	19.792	20.218	20.644				
500	20.644	21.071	21.497	21.924	22.350	22.776	23.203	23.629	24.055	24.480	24.905				
600	24.905	25.330	25.755	26.179	26.602	27.025	27.447	27.869	28.289	28.710	29.129				
700	29.129	29.548	29.965	30.382	30.798	31.213	31.628	32.041	32.453	32.865	33.275				
800	33.275	33.685	34.093	34.501	34.908	35.313	35.718	36.121	36.524	36.925	37.326				
900	37.326	37.725	38.124	38.522	38.918	39.314	39.708	40.101	40.494	40.885	41.276				
1000	41.276	41.665	42.053	42.440	42.826	43.211	43.595	43.978	44.359	44.740	45.119				
1100	45.119	45.497	45.873	46.249	46.623	46.995	47.367	47.737	48.105	48.473	48.838				
1200	48.838	49.202	49.565	49.926	50.286	50.644	51.000	51.355	51.708	52.060	52.410				
1300	52.410	52.759	53.106	53.451	53.795	54.138	54.479	54.819							

Temperature ranges and coefficients of equations used to compute the above table: The equations are of the form: $E = c_0 + c_1 t + c_2 t^2 + c_3 t^3 + \dots + c_n t^n$, where E is the emf in millivolts, t is the temperature in degrees Celsius (ITS-90), and $c_0, c_1, c_2, c_3, \dots$ etc. are the coefficients. In the 0°C to 1372°C range there is also an exponential

term that must be evaluated and added to the equation. The exponential term is of the form: $c_0 e^{c_1(t-126.9686)^2}$, where t is the temperature in °C, e is the natural logarithm base, and c_0 and c_1 are the coefficients. These coefficients are extracted from Reference 1.

		-270°C to 0°C	0°C to 1372°C	0°C to 1372°C (Exponential term)
c ₀	=	0.000 000 000 0	-1.760 041 368 6 × 10 ⁻²	1.185 976 × 10 ⁻¹
c ₁	=	3.945 012 802 5 × 10 ⁻²	3.892 120 497 5 × 10 ⁻²	-1.183 432 × 10 ⁻⁴
c ₂	=	2.362 237 359 8 × 10 ⁻⁵	1.855 877 003 2 × 10 ⁻⁵
c ₃	=	-3.285 890 678 4 × 10 ⁻⁷	-9.945 759 287 4 × 10 ⁻⁸
c ₄	=	-4.990 482 877 7 × 10 ⁻⁹	3.184 094 571 9 × 10 ⁻¹⁰
c ₅	=	-6.750 905 917 3 × 10 ⁻¹¹	-5.607 284 488 9 × 10 ⁻¹³
c ₆	=	-5.741 032 742 8 × 10 ⁻¹³	5.607 505 905 9 × 10 ⁻¹⁶
c ₇	=	-3.108 887 289 4 × 10 ⁻¹⁵	-3.202 072 000 3 × 10 ⁻¹⁹
c ₈	=	-1.045 160 936 5 × 10 ⁻¹⁷	9.715 114 715 2 × 10 ⁻²³
c ₉	=	-1.988 926 687 8 × 10 ⁻²⁰	-1.210 472 127 5 × 10 ⁻²⁶
c ₁₀	=	-1.632 269 748 6 × 10 ⁻²³

Type N Thermocouples: emf-Temperature (°C) Reference Table and Equations

Thermocouple emf as a Function of Temperature in Degrees Celsius (ITS-90)

emf in Millivolts										Reference junctions at 0 °C			
°C	0	-10	-20	-30	-40	-50	-60	-70	-80	-90	-100		
-200	3.990	-4.083	-4.162	-4.226	-4.277	-4.313	-4.336	-4.345					
-100	-2.407	-2.612	2.808	2.994	3.171	3.336	-3.491	3.634	-3.766	-3.884	-3.990		
0	0.000	-0.260	-0.518	-0.772	-1.023	-1.269	-1.509	1.744	-1.972	-2.193	-2.407		
°C	0	10	20	30	40	50	60	70	80	90	100		
0	0.000	0.261	0.525	0.793	1.065	1.340	1.619	1.902	2.189	2.480	2.774		
100	2.774	3.072	3.374	3.680	3.989	4.302	4.618	4.937	5.259	5.585	5.913		
200	5.913	6.245	6.579	6.916	7.255	7.597	7.941	8.288	8.637	8.988	9.341		
300	9.341	9.696	10.054	10.413	10.774	11.136	11.501	11.867	12.234	12.603	12.974		
400	12.974	13.346	13.719	14.094	14.469	14.846	15.225	15.604	15.984	16.366	16.748		
500	16.748	17.131	17.515	17.900	18.286	18.672	19.059	19.447	19.835	20.224	20.613		
600	20.613	21.003	21.393	21.784	22.175	22.566	22.958	23.350	23.742	24.134	24.527		
700	24.527	24.919	25.312	25.705	26.098	26.491	26.883	27.276	27.669	28.062	28.455		
800	28.455	28.847	29.239	29.632	30.024	30.416	30.807	31.199	31.590	31.981	32.371		
900	32.371	32.761	33.151	33.541	33.930	34.319	34.707	35.095	35.482	35.869	36.256		
1000	36.256	36.641	37.027	37.411	37.795	38.179	38.562	38.944	39.326	39.706	40.087		
1100	40.087	40.466	40.845	41.223	41.600	41.976	42.352	42.727	43.101	43.474	43.846		
1200	43.846	44.218	44.588	44.958	45.326	45.694	46.060	46.425	46.789	47.152	47.513		
1300	47.513												

Temperature ranges and coefficients of equations used to compute the above table: The equations are of the form: E = c₀ + c₁t + c₂t² + c₃t³ + ... c_ntⁿ, where E is the emf in millivolts, t is the tem-

perature in degrees Celsius (ITS-90), and c₀, c₁, c₂, c₃, etc. are the coefficients. These coefficients are extracted from Reference 1.

	-270°C to 0°C	0°C to 1300°C
c ₀	= 0.000 000 000 0 ...	0.000 000 000 0 ...
c ₁	= 2.615 910 596 2 × 10 ⁻²	2.592 939 460 1 × 10 ⁻²
c ₂	= 1.095 748 422 8 × 10 ⁻⁵	1.571 014 188 0 × 10 ⁻⁵
c ₃	= -9.384 111 155 4 × 10 ⁻⁸	4.382 562 723 7 × 10 ⁻⁸
c ₄	= -4.641 203 975 9 × 10 ⁻¹¹	-2.526 116 979 4 × 10 ⁻¹⁰
c ₅	= -2.630 335 771 6 × 10 ⁻¹²	6.431 181 933 9 × 10 ⁻¹³
c ₆	= -2.265 343 800 3 × 10 ⁻¹⁴	-1.006 347 151 9 × 10 ⁻¹⁵
c ₇	= -7.608 930 079 1 × 10 ⁻¹⁷	9.974 533 899 2 × 10 ⁻¹⁹
c ₈	= -9.341 966 783 5 × 10 ⁻²⁰	-6.086 324 560 7 × 10 ⁻²²
c ₉	=	2.084 922 933 9 × 10 ⁻²⁵
c ₁₀	=	-3.068 219 615 1 × 10 ⁻²⁹

Type R Thermocouples: emf-Temperature (°C) Reference Table and Equations

Thermocouple emf as a Function of Temperature in Degrees Celsius (ITS-90)

emf in Millivolts											Reference junctions at 0 °C				
°C	0	-10	-20	-30	-40	-50	-60	-70	-80	-90	-100				
0	0.000	-0.051	-0.100	-0.145	-0.188	-0.226									
100	0.647	0.723	0.800	0.879	0.959	1.041	1.124	1.208	1.294	1.381	1.469				
200	1.469	1.558	1.648	1.739	1.831	1.923	2.017	2.112	2.207	2.304	2.401				
300	2.401	2.498	2.597	2.696	2.796	2.896	2.997	3.099	3.201	3.304	3.408				
400	3.408	3.512	3.616	3.721	3.827	3.933	4.040	4.147	4.255	4.363	4.471				
500	4.471	4.580	4.690	4.800	4.910	5.021	5.133	5.245	5.357	5.470	5.583				
600	5.583	5.697	5.812	5.926	6.041	6.157	6.273	6.390	6.507	6.625	6.743				
700	6.743	6.861	6.980	7.100	7.220	7.340	7.461	7.583	7.705	7.827	7.950				
800	7.950	8.073	8.197	8.321	8.446	8.571	8.697	8.823	8.950	9.077	9.205				
900	9.205	9.333	9.461	9.590	9.720	9.850	9.980	10.111	10.242	10.374	10.506				
1000	10.506	10.638	10.771	10.905	11.039	11.173	11.307	11.442	11.578	11.714	11.850				
1100	11.850	11.986	12.123	12.260	12.397	12.535	12.673	12.812	12.950	13.089	13.228				
1200	13.228	13.367	13.507	13.646	13.786	13.926	14.066	14.207	14.347	14.488	14.629				
1300	14.629	14.770	14.911	15.052	15.193	15.334	15.475	15.616	15.758	15.899	16.040				
1400	16.040	16.181	16.323	16.464	16.605	16.746	16.887	17.028	17.169	17.310	17.451				
1500	17.451	17.591	17.732	17.872	18.012	18.152	18.292	18.431	18.571	18.710	18.849				
1600	18.849	18.988	19.126	19.264	19.402	19.540	19.677	19.814	19.951	20.087	20.222				
1700	20.222	20.356	20.488	20.620	20.749	20.877	21.003								

Temperature ranges and coefficients of equations used to compute the above table: The equations are of the form: $E = c_0 + c_1 t + c_2 t^2 + c_3 t^3 + \dots + c_n t^n$, where E is the emf in millivolts, t is the temperature in degrees Celsius (ITS-90), and c_0, c_1, c_2, c_3 , etc. are the coefficients. These coefficients are extracted from Reference 1.

	-50°C to 1064.18°C	1064.18°C to 1664.5°C	1664.5°C to 1768.1°C
c_0	= 0.000 000 000 00 ...	2.951 579 253 16 ...	1.522 321 182 09 $\times 10^2$
c_1	= 5.289 617 297 65 $\times 10^{-3}$	-2.520 612 513 32 $\times 10^{-3}$	-2.688 198 885 45 $\times 10^{-1}$
c_2	= 1.391 665 897 82 $\times 10^{-5}$	1.595 645 018 65 $\times 10^{-5}$	1.712 802 804 71 $\times 10^{-4}$
c_3	= -2.388 556 930 17 $\times 10^{-8}$	-7.640 859 475 76 $\times 10^{-9}$	-3.458 957 064 53 $\times 10^{-8}$
c_4	= 3.569 160 010 63 $\times 10^{-11}$	2.053 052 910 24 $\times 10^{-12}$	-9.346 339 710 46 $\times 10^{-15}$
c_5	= -4.623 476 662 98 $\times 10^{-14}$	-2.933 596 681 73 $\times 10^{-16}$
c_6	= 5.007 774 410 34 $\times 10^{-17}$
c_7	= -3.731 058 861 91 $\times 10^{-20}$
c_8	= 1.577 164 823 67 $\times 10^{-23}$
c_9	= -2.810 386 252 51 $\times 10^{-27}$

Type S Thermocouples: emf-Temperature (°C) Reference Table and Equations.

Thermocouple emf as a Function of Temperature in Degrees Celsius (ITS-90)

emf in Millivolts											Reference junctions at 0 °C				
°C	0	-10	-20	-30	-40	-50	-60	-70	-80	-90	-100				
0	0.000	-0.053	-0.103	-0.150	-0.194	-0.236									
100	0.646	0.720	0.795	0.872	0.950	1.029	1.110	1.191	1.273	1.357	1.441				
200	1.441	1.526	1.612	1.698	1.786	1.874	1.962	2.052	2.141	2.232	2.323				
300	2.323	2.415	2.507	2.599	2.692	2.786	2.880	2.974	3.069	3.164	3.259				
400	3.259	3.355	3.451	3.548	3.645	3.742	3.840	3.938	4.036	4.134	4.233				
500	4.233	4.332	4.432	4.532	4.632	4.732	4.833	4.934	5.035	5.137	5.239				
600	5.239	5.341	5.443	5.546	5.649	5.753	5.857	5.961	6.065	6.170	6.275				
700	6.275	6.381	6.486	6.593	6.699	6.806	6.913	7.020	7.128	7.236	7.345				
800	7.345	7.454	7.563	7.673	7.783	7.893	8.003	8.114	8.226	8.337	8.449				
900	8.449	8.562	8.674	8.787	8.900	9.014	9.128	9.242	9.357	9.472	9.587				
1000	9.587	9.703	9.819	9.935	10.051	10.168	10.285	10.403	10.520	10.638	10.757				
1100	10.757	10.875	10.994	11.113	11.232	11.351	11.471	11.590	11.710	11.830	11.951				
1200	11.951	12.071	12.191	12.312	12.433	12.554	12.675	12.796	12.917	13.038	13.159				

Type S Thermocouples: emf-Temperature (°C) Reference Table and Equations.

Thermocouple emf as a Function of Temperature in Degrees Celsius (ITS-90)

°C	emf in Millivolts										Reference junctions at 0 °C				
	0	-10	-20	-30	-40	-50	-60	-70	-80	-90	-100				
1300	13.159	13.280	13.402	13.523	13.644	13.766	13.887	14.009	14.130	14.251	14.373				
1400	14.373	14.494	14.615	14.736	14.857	14.978	15.099	15.220	15.341	15.461	15.582				
1500	15.582	15.702	15.822	15.942	16.062	16.182	16.301	16.420	16.539	16.658	16.777				
1600	16.777	16.895	17.013	17.131	17.249	17.366	17.483	17.600	17.717	17.832	17.947				
1700	17.947	18.061	18.174	18.285	18.395	18.503	18.609								

Temperature ranges and coefficients of equations used to compute the above table: The equations are of the form: $E = c_0 + c_1t + c_2t^2 + c_3t^3 + \dots + c_nt^n$, where E is the emf in millivolts, t is the tem-

perature in degrees Celsius (ITS-90), and c_0, c_1, c_2, c_3 , etc. are the coefficients. These coefficients are extracted from Reference 1.

-50°C to 1064.18°C			1064.18°C to 1664.5°C			1664.5°C to 1768.1°C		
c_0	=	0.000 000 000 00 ...	1.329 004 440 85 ...			1.466 282 326 36 $\times 10^2$		
c_1	=	5.403 133 086 31 $\times 10^{-3}$	3.345 093 113 44 $\times 10^{-3}$			-2.584 305 167 52 $\times 10^{-1}$		
c_2	=	1.259 342 897 40 $\times 10^{-5}$	6.548 051 928 18 $\times 10^{-6}$			1.636 935 746 41 $\times 10^{-4}$		
c_3	=	-2.324 779 686 89 $\times 10^{-8}$	-1.648 562 592 09 $\times 10^{-9}$			-3.304 390 469 87 $\times 10^{-8}$		
c_4	=	3.220 288 230 36 $\times 10^{-11}$	1.299 896 051 74 $\times 10^{-14}$			-9.432 236 906 12 $\times 10^{-15}$		
c_5	=	-3.314 651 963 89 $\times 10^{-14}$		
c_6	=	2.557 442 517 86 $\times 10^{-17}$		
c_7	=	-1.250 688 713 93 $\times 10^{-20}$		
c_8	=	2.714 431 761 45 $\times 10^{-24}$		

Type T Thermocouples: emf-Temperature (°C) Reference Table and Equations.

Thermocouple emf as a Function of Temperature in Degrees Celsius (ITS-90)

°C	emf in Millivolts										Reference junctions at 0 °C				
	0	-10	-20	-30	-40	-50	-60	-70	-80	-90	-100				
-200	-5.603	-5.753	-5.888	-6.007	-6.105	-6.180	-6.232	-6.258							
-100	-3.379	-3.657	-3.923	-4.177	-4.419	-4.648	-4.865	-5.070	-5.261	-5.439	-5.603				
0	0.000	-0.383	-0.757	-1.121	-1.475	-1.819	-2.153	-2.476	-2.788	-3.089	-3.379				
°C	0	10	20	30	40	50	60	70	80	90	100				
0	0.000	0.391	0.790	1.196	1.612	2.036	2.468	2.909	3.358	3.814	4.279				
100	4.279	4.750	5.228	5.714	6.206	6.704	7.209	7.720	8.237	8.759	9.288				
200	9.288	9.822	10.362	10.907	11.458	12.013	12.574	13.139	13.709	14.283	14.862				
300	14.862	15.445	16.032	16.624	17.219	17.819	18.422	19.030	19.641	20.255	20.872				
400		20.872													

Temperature ranges and coefficients of equations used to compute the above table: The equations are of the form: $E = c_0 + c_1t + c_2t^2 + c_3t^3 + \dots + c_nt^n$, where E is the emf in millivolts, t is the tem-

perature in degrees Celsius (ITS-90), and c_0, c_1, c_2, c_3 , etc. are the coefficients. These coefficients are extracted from Reference 1.

270 °C to 0 °C			0 °C to 400 °C		
c_0	=	0.000 000 000 0 ...	0.000 000 000 0 ...		
c_1	=	3.874 810 636 4 $\times 10^{-2}$	3.874 810 636 4 $\times 10^{-2}$		
c_2	=	4.419 443 434 7 $\times 10^{-5}$	3.329 222 788 0 $\times 10^{-5}$		
c_3	=	1.184 432 310 5 $\times 10^{-7}$	2.061 824 340 4 $\times 10^{-7}$		
c_4	=	2.003 297 355 4 $\times 10^{-8}$	-2.188 225 684 6 $\times 10^{-9}$		
c_5	=	9.013 801 955 9 $\times 10^{-10}$	1.099 688 092 8 $\times 10^{-11}$		
c_6	=	2.265 115 659 3 $\times 10^{-11}$	-3.081 575 877 2 $\times 10^{-14}$		
c_7	=	3.607 115 420 5 $\times 10^{-13}$	4.547 913 529 0 $\times 10^{-17}$		
c_8	=	3.849 393 988 3 $\times 10^{-15}$	-2.751 290 167 3 $\times 10^{-20}$		
c_9	=	2.821 352 192 5 $\times 10^{-17}$		
c_{10}	=	1.425 159 477 9 $\times 10^{-19}$		
c_{11}	=	4.876 866 228 6 $\times 10^{-22}$		
c_{12}	=	1.079 553 927 0 $\times 10^{-24}$		
c_{13}	=	1.394 502 706 2 $\times 10^{-27}$		
c_{14}	=	7.979 515 392 7 $\times 10^{-31}$		

Type B Thermocouples: Coefficients (c_i) of Polynomials for the Computation of Temperatures in °C as a Function of the Thermocouple emf in Various Temperature and emf Ranges

Temperature range:	250 °C to 700 °C	700 °C to 1820 °C
emf range:	0.291 mV to 2.431 mV	2.431 mV to 13.820 mV
$c_0 =$	$9.842\ 332\ 1 \times 10^1$	$2.131\ 507\ 1 \times 10^2$
$c_1 =$	$6.997\ 150\ 0 \times 10^2$	$2.851\ 050\ 4 \times 10^2$
$c_2 =$	$-8.476\ 530\ 4 \times 10^2$	$-5.274\ 288\ 7 \times 10^1$
$c_3 =$	$1.005\ 264\ 4 \times 10^3$	$9.916\ 080\ 4 \dots$
$c_4 =$	$-8.334\ 595\ 2 \times 10^2$	$-1.296\ 530\ 3 \dots$
$c_5 =$	$4.550\ 854\ 2 \times 10^2$	$1.119\ 587\ 0 \times 10^{-1}$
$c_6 =$	$-1.552\ 303\ 7 \times 10^2$	$-6.062\ 519\ 9 \times 10^{-3}$
$c_7 =$	$2.988\ 675\ 0 \times 10^1$	$1.866\ 169\ 6 \times 10^{-4}$
$c_8 =$	$-2.474\ 286\ 0 \dots$	$-2.487\ 858\ 5 \times 10^{-6}$

NOTE— The above coefficients are extracted from Reference 1 and are for an expression of the form shown in Section 10.3.2. They yield approximate values of temperature that agree within ± 0.03 °C with the values given in Table 10.2.

Type E Thermocouples: Coefficients (c_i) of Polynomials for the Computation of Temperatures in °C as a Function of the Thermocouple emf in Various Temperature and emf Ranges

Temperature range:	-200 °C TO 0 °C	0 °C to 1000 °C
emf range:	-8.825 mV to 0.0 mV	0.0 mV to 76.373 mV
$c_0 =$	$0.000\ 000\ 0 \dots$	$0.000\ 000\ 0 \dots$
$c_1 =$	$1.697\ 728\ 8 \times 10^1$	$1.705\ 703\ 5 \times 10^1$
$c_2 =$	$-4.351\ 497\ 0 \times 10^{-1}$	$-2.330\ 175\ 9 \times 10^{-1}$
$c_3 =$	$-1.585\ 969\ 7 \times 10^{-1}$	$6.543\ 558\ 5 \times 10^{-3}$
$c_4 =$	$-9.250\ 287\ 1 \times 10^{-2}$	$-7.356\ 274\ 9 \times 10^{-5}$
$c_5 =$	$-2.608\ 431\ 4 \times 10^{-2}$	$-1.789\ 600 \times 10^{-6}$
$c_6 =$	$-4.136\ 019\ 9 \times 10^{-3}$	$8.403\ 616\ 5 \times 10^{-8}$
$c_7 =$	$-3.403\ 403\ 0 \times 10^{-4}$	$-1.373\ 587\ 9 \times 10^{-9}$
$c_8 =$	$-1.156\ 489\ 0 \times 10^{-5}$	$1.062\ 982\ 3 \times 10^{-11}$
$c_9 =$	$-3.244\ 708\ 7 \times 10^{-14}$

NOTE— The above coefficients are extracted from Reference 1 and are for an expression of the form shown in Section 10.3.2. They yield approximate values of temperature that agree within ± 0.02 °C with the values given in Table 10.4

Type J Thermocouples: Coefficients (c_i) of Polynomials for the Computation of Temperatures in °C as a Function of the Thermocouple emf in Various Temperature and emf Ranges

Temperature range:	-210 °C to 0 °C	0 °C to 760 °C	760 °C to 1200 °C
emf Range:	-8.095 mV to 0.0 mV	0.0 mV to 42.919 mV	42.919 mV to 69.553 mV
$c_0 =$	$0.000\ 000\ 0 \dots$	$0.000\ 000 \dots$	$-3.113\ 581\ 87 \times 10^3$
$c_1 =$	$1.952\ 826\ 8 \times 10^1$	$1.978\ 425 \times 10^1$	$3.005\ 436\ 84 \times 10^2$
$c_2 =$	$-1.228\ 618\ 5 \dots$	$-2.001\ 204 \times 10^{-1}$	$-9.947\ 732\ 30 \dots$
$c_3 =$	$-1.075\ 217\ 8 \dots$	$1.036\ 969 \times 10^{-2}$	$1.702\ 766\ 30 \times 10^{-1}$
$c_4 =$	$-5.908\ 693\ 3 \times 10^{-1}$	$-2.549\ 687 \times 10^{-4}$	$1.430\ 334\ 68 \times 10^{-3}$
$c_5 =$	$-1.725\ 671\ 3 \times 10^{-1}$	$3.585\ 153 \times 10^{-6}$	$4.438\ 860\ 84 \times 10^{-6}$
$c_6 =$	$-2.813\ 151\ 3 \times 10^{-2}$	$-5.344\ 285 \times 10^{-8}$
$c_7 =$	$-2.396\ 337\ 0 \times 10^{-3}$	$5.099\ 890 \times 10^{-10}$
$c_8 =$	$-8.382\ 332\ 1 \times 10^{-5}$

NOTE— The above coefficients are extracted from Reference 1 and are for an expression of the form shown in Section 10.3.2. They yield approximate values of temperature that agree within ± 0.5 °C with the values given in Table 10.6.

Type K Thermocouples: Coefficients (c_i) of Polynomials for the Computation of Temperatures in °C as a Function of the Thermocouple emf in Various Temperature and emf Ranges

Temperature range:	-200 °C to 0 °C	0 °C to 500 °C	500 °C to 1372 °C
emf Range:	-5.891 mV to 0.0 mV	0.0 mV to 20.644 mV	20.644 mV to 54.886 mV
$c_0 =$	0.000 000 0 ...	0.000 000 ...	$-1.318\ 058 \times 10^2$
$c_1 =$	$2.517\ 346\ 2 \times 10^1$	$2.508\ 355 \times 10^1$	$4.830\ 222 \times 10^1$
$c_2 =$	$-1.166\ 287\ 8 \dots$	$7.860\ 106 \times 10^{-2}$	$-1.646\ 031 \dots$
$c_3 =$	$-1.083\ 363\ 8 \dots$	$-2.503\ 131 \times 10^{-1}$	$5.464\ 731 \times 10^{-2}$
$c_4 =$	$-8.977\ 354\ 0 \times 10^{-1}$	$8.315\ 270 \times 10^{-2}$	$-9.650\ 715 \times 10^{-4}$
$c_5 =$	$-3.734\ 237\ 7 \times 10^{-1}$	$-1.228\ 034 \times 10^{-2}$	$8.802\ 193 \times 10^{-6}$
$c_6 =$	$-8.663\ 264\ 3 \times 10^{-2}$	$9.804\ 036 \times 10^{-4}$	$3.110\ 810 \times 10^{-8}$
$c_7 =$	$-1.045\ 059\ 8 \times 10^{-2}$	$-4.413\ 030 \times 10^{-5}$
$c_8 =$	$-5.192\ 057\ 7 \times 10^{-4}$	$1.057\ 734 \times 10^{-6}$
$c_9 =$	$-1.052\ 755 \times 10^{-8}$

NOTE—The above coefficients are extracted from Reference 1 and are for an expression of the form shown in Section 10.3.2. They yield approximate values of temperature that agree within ± 0.05 °C with the values given in Table 10.8.

Type N Thermocouples: Coefficients (c_i) of Polynomials for the Computation of Temperatures in °C as a Function of the Thermocouple emf in Various Temperature and emf Ranges

Temperature range:	-200 °C to 0 °C	0 °C to 600 °C	600 °C to 1300 °C
emf Range:	-3.990 mV to 0.0 mV	0.0 mV to 20.613 mV	20.613 mV to 47.513 mV
$c_0 =$	0.000 000 0 ...	0.000 00 ...	$1.972\ 485 \times 10^1$
$c_1 =$	$3.843\ 684\ 7 \times 10^1$	$3.868\ 96 \times 10^1$	$3.300\ 943 \times 10^1$
$c_2 =$	$1.101\ 048\ 5 \dots$	$-1.082\ 67 \dots$	$-3.915\ 159 \times 10^{-1}$
$c_3 =$	$5.222\ 931\ 2 \dots$	$4.702\ 05 \times 10^{-2}$	$9.855\ 391 \times 10^{-3}$
$c_4 =$	$7.206\ 052\ 5 \dots$	$-2.121\ 69 \times 10^{-6}$	$-1.274\ 371 \times 10^{-4}$
$c_5 =$	$5.848\ 858\ 6 \dots$	$-1.172\ 72 \times 10^{-4}$	$7.767\ 022 \times 10^{-7}$
$c_6 =$	$2.775\ 491\ 6 \dots$	$5.392\ 80 \times 10^{-6}$
$c_7 =$	$7.707\ 516\ 6 \times 10^{-1}$	$-7.981\ 56 \times 10^{-8}$
$c_8 =$	$1.158\ 266\ 5 \times 10^{-1}$
$c_9 =$	$7.313\ 886\ 8 \times 10^{-3}$

NOTE—The above coefficients are extracted from Reference 1 and are for an expression of the form shown in Section 10.3.2. They yield approximate values of temperature that agree within ± 0.04 °C with the values given in Table 10.10.

Type R Thermocouples: Coefficients (c_i) of Polynomials for the Computation of Temperatures in °C as a Function of the Thermocouple emf in Various Temperature and emf Ranges

Temperature range:	-50 °C to 250 °C	250 °C to 1200 °C	1064°C to 1664.5 °C	1664.5 °C to 1768.1 °C
emf Range:	-0.226 mV to 1.923 mV	1.923 mV to 13.228 mV	11.361 mV to 19.739 mV	19.739 mV to 21.103 mV
$c_0 =$	0.000 000 0 ...	$1.334\ 584\ 505 \times 10^1$	$-8.199\ 599\ 416 \times 10^1$	$3.406\ 177\ 836 \times 10^4$
$c_1 =$	$1.889\ 138\ 0 \times 10^2$	$1.472\ 644\ 573 \times 10^2$	$1.553\ 962\ 042 \times 10^2$	$-7.023\ 729\ 171 \times 10^3$
$c_2 =$	$-9.383\ 529\ 0 \times 10^1$	$-1.844\ 024\ 844 \times 10^1$	$-8.342\ 197\ 663$	$5.582\ 903\ 813 \times 10^2$
$c_3 =$	$1.306\ 861\ 9 \times 10^2$	$4.031\ 129\ 726 \dots$	$4.279\ 433\ 549 \times 10^{-1}$	$-1.952\ 394\ 635 \times 10^1$
$c_4 =$	$-2.270\ 358\ 0 \times 10^2$	$-6.249\ 428\ 360 \times 10^{-1}$	$-1.191\ 577\ 910 \times 10^{-2}$	$2.560\ 740\ 231 \times 10^{-1}$
$c_5 =$	$3.514\ 565\ 9 \times 10^2$	$6.468\ 412\ 046 \times 10^{-2}$	$1.492\ 290\ 091 \times 10^{-4}$
$c_6 =$	$-3.895\ 390\ 0 \times 10^2$	$-4.458\ 750\ 426 \times 10^{-3}$
$c_7 =$	$2.823\ 947\ 1 \times 10^2$	$1.994\ 710\ 149 \times 10^{-4}$
$c_8 =$	$-1.260\ 728\ 1 \times 10^2$	$-5.313\ 401\ 790 \times 10^{-6}$
$c_9 =$	$3.135\ 361\ 1 \times 10^1$	$6.481\ 976\ 217 \times 10^{-8}$
$c_{10} =$	$-3.318\ 776\ 9 \dots$

NOTE—The above coefficients are extracted from Reference 1 and are for an expression of the form shown in Section 10.3.2. They yield approximate values of temperature that agree within ± 0.02 °C with the values given in Table 10.12.

Type S Thermocouples: Coefficients (c_i) of Polynomials for the Computation of Temperatures in °C as a Function of the Thermocouple emf in Various Temperature and emf Ranges

Temperature range: emf Range:	-50 °C to 250 °C -0.235 mV to 1.874 mV	250 °C to 1200 °C 1.874 mV to 11.950 mV	1064 °C to 1664.5 °C 10.332 mV to 17.536 mV	1664.5 °C to 1768.1 °C 17.536 mV to 18.693 mV
$c_0 =$	0.000 000 00 . . .	$1.291\ 507\ 177 \times 10^1$	$-8.087\ 801\ 117 \times 10^1$	$5.333\ 875\ 126 \times 10^4$
$c_1 =$	$1.849\ 494\ 60 \times 10^2$	$1.466\ 298\ 863 \times 10^2$	$1.621\ 573\ 104 \times 10^2$	$-1.235\ 892\ 298 \times 10^4$
$c_2 =$	$-8.005\ 040\ 62 \times 10^1$	$-1.534\ 713\ 402 \times 10^1$	$-8.536\ 869\ 453 . . .$	$1.092\ 657\ 613 \times 10^3$
$c_3 =$	$1.022\ 374\ 30 \times 10^2$	$3.145\ 945\ 973 . . .$	$4.719\ 686\ 976 \times 10^{-1}$	$-4.265\ 693\ 686 \times 10^1$
$c_4 =$	$-1.522\ 485\ 92 \times 10^2$	$-4.163\ 257\ 839 \times 10^{-1}$	$-1.441\ 693\ 666 \times 10^2$	$6.247\ 205\ 420 \times 10^{-1}$
$c_5 =$	$1.888\ 213\ 43 \times 10^2$	$3.187\ 963\ 771 \times 10^{-2}$	$2.081\ 618\ 890 \times 10^{-4}$
$c_6 =$	$-1.590\ 859\ 41 \times 10^2$	$-1.291\ 637\ 500 \times 10^{-3}$
$c_7 =$	$8.230\ 278\ 80 \times 10^1$	$2.183\ 475\ 087 \times 10^{-5}$
$c_8 =$	$-2.341\ 819\ 44 \times 10^1$	$-1.447\ 379\ 511 \times 10^{-7}$
$c_9 =$	$2.797\ 862\ 60 . . .$	$8.211\ 272\ 125 \times 10^{-9}$

NOTE—The above coefficients are extracted from Reference 1 and are for an expression of the form shown in Section 10.3.2. They yield approximate values of temperature that agree within ± 0.02 °C with the values given in Table 10.14.

Type T Thermocouples: Coefficients (c_i) of Polynomials for the Computation of temperatures in °C as a Function of the Thermocouple emf in Various Temperature and emf Ranges

Temperature range: emf Range:	-200 °C to 0 °C -5.603 mV to 0.0 mV	0 °C to 400 °C 0.0 mV to 20.872 mV
$c_0 =$	0.000 000 0 . . .	0.000 000 . . .
$c_1 =$	$2.594\ 919\ 2 \times 10^1$	$2.592\ 800 \times 10^1$
$c_2 =$	$-2.131\ 696\ 7 \times 10^{-1}$	$-7.602\ 961 \times 10^{-1}$
$c_3 =$	$7.901\ 869\ 2 \times 10^{-1}$	$4.637\ 791 \times 10^{-2}$
$c_4 =$	$4.252\ 777\ 7 \times 10^{-1}$	$-2.165\ 394 \times 10^{-3}$
$c_5 =$	$1.330\ 447\ 3 \times 10^{-1}$	$6.048\ 144 \times 10^{-5}$
$c_6 =$	$2.024\ 144\ 6 \times 10^{-2}$	$-7.293\ 422 \times 10^{-7}$
$c_7 =$	$1.266\ 817\ 1 \times 10^{-3}$

NOTE—The above coefficients are extracted from Reference 1 and are for an expression of the form shown in Section 10.3.2. They yield approximate values of temperature that agree within ± 0.04 °C with the values given in Table 10.16.